## Keystone Jack, CAT 6a De Embedded, tool free connection

Part No.: DN-93612



## **Attributes**

Cable Entry: Rear

Hole Plate Thickness: Jack will clip into a hole plate thickness of 1.6mm Max

Body: Zinc Die-casting, nickel-plated

Jack Contacts: Phosphor Bronze IDC Contacts: Phosphor Bronze

Plating:  $50\mu m$  of gold over  $40\mu m$  of nickel

Wire Terminations: Tool Free with Cap.
Wiring Standard: EIA/TIA 568A/B

Conformance: Category 6a / 10GBase-T Channel

ANSI/EIA/TIA 568B.2.1:2002 ISO/IEC 11801:2002 EN50173-1: 2002

Certification: Independent Laboratory
Dimension: 18x24x41mm
Weight: ca. 23g

## **Shielded Keystone Jack**

The fully downward compatible CAT 6a Keystone Jacks makes an easy installation in combination with excellent measurements possible. The Keystone Jack supports all current and further standards like 10GBase-T. The innovative housing design offers quick and safe wire terminations without usage of any special tools. Its compact form allows a usage of 24 Keystone Jacks in a row with a 19" 1U Patch Panel. These facts ensure an uncomplicated mounting and marking as well as a high reliability.







